

# DF 132

## DOUBLE-COATED PE FOAM TAPE

### TYPICAL APPLICATIONS

- Vibration reduction
- Gap filling
- General purpose mounting

### PRODUCT FEATURES

- Superior adhesion to a variety of surfaces, including low-surface energy materials like PE and PP
- Excellent conformability
- Good moisture resistance

### CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: 1/32 in closed cell polyethylene foam

Adhesive: Rubber-based

Liner: 83-lb. super calendered kraft

### STANDARD WIDTH(S)

12 mm    18 mm    24 mm

### STANDARD LENGTH(S)

72 yd

Contact your Shurtape sales representative for other available sizes

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	213 lbs/in width	3730 N/10 mm
Adhesion to Stainless Steel	137 oz/in width	150 N/10 mm
Thickness (With Liner)	39.25 mils	1.00 mm
Elongation	355%	355%
Service Temperature Range	0 F to 180 F	-18 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

