

DF 164



DOUBLE-COATED PE FOAM TAPE

TYPICAL APPLICATIONS

- Vibration reduction
- Gap filling
- General purpose mounting

PRODUCT FEATURES

- Superior adhesion to a variety of surfaces, including low-surface energy materials like PE and PP
- Excellent conformability
- Good moisture resistance

CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: 1/16 in closed cell polyethylene foam

Adhesive: Rubber-based

Liner: 83-lb. super calendered kraft

STANDARD WIDTH(S)

12 mm 19 mm 24 mm

STANDARD LENGTH(S)

36 yd

Contact your Shurtape sales representative for other available sizes


STANDARD CORE SIZE

3 in

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	145 lbs/in width	2539 N/10 mm
Adhesion to Stainless Steel	137 oz/in width	150 N/10 mm
Thickness (With Liner)	70.5 mils	1.79 mm
Elongation	339%	339%
Service Temperature Range	0 F to 180 F	-18 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

