

FP 202



PACKAGING PREMIUM GRADE BLEACHED FLATBACK PAPER TAPE



TYPICAL APPLICATIONS

- For splicing various substrates
- Also used for heavy duty hand and machine carton sealing applications
- Also used for general purpose applications where a thick, flatback paper tape is required
- Meets or exceeds requirements for motor freight, railway, air express, air freight, postal shipments and government packaging when used as a carton sealing tape

PRODUCT FEATURES

- Very high adhesion
- Excellent quick stick
- Resistant to abrasion, water, solvents and oil

CONSTRUCTION

Overall Grade/Function: Packaging Premium
Backing: Heavy duty bleached flatback paper
Adhesive: Rubber-based

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m 110 m

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II; ASTM D 5486M-12, Type V

COLOR(S)



PHYSICAL PROPERTIES STANDARD METRIC

Tensile Strength	56 lbs/in width	6.13 N/10 mm
Adhesion to Stainless Steel	56 oz/in width	6.13 N/10 mm
Thickness	7.5 mils	0.19 mm
Elongation	3%	3%
Service Temperature Range	50 F to 180 F	10 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

