

PE 100

Shurtape®
TRUE TO YOUR WORK™

FLOORMATE® TEMPORARY FLOOR TAPE

TYPICAL APPLICATIONS

- For use on properly prepared and cured wood floors/finishes
- Also used as a gym floor marking tape for creating temporary lines and boundaries
- Can also be used on other hard flooring surfaces, including sheet vinyl, wood laminates, engineered hardwood, tile, marble and granite
- CAUTION: Test tape in an inconspicuous area before using. Temporary use only. Finish damage is difficult/expensive to repair on wood floors, so assure preparation and finish application are done per finish manufacturer's recommendations. Allow finish to cure fully before applying tape. Remove tape slowly prior to 30 days on the floor. Please refer to the list of Lab-Tested Finishes.

PRODUCT FEATURES

- Low adhesion
- Conformable
- Will not tear or splinter
- 30-day residue-free removal without surface damage
- Durable

CONSTRUCTION

Overall Grade/Function: Specialty
Backing: Modified polyethylene
Adhesive: Acrylic-based

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

60 yd

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



WHITE
(WHI)



BLACK
(BLK)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	11 lbs/in width	19.3 N/10 mm
Adhesion to Stainless Steel	15 oz/in width	1.64 N/10 mm
Thickness	4.6 mils	0.12 mm
Elongation	500%	500%
Water Vapor Transmission Rate	0.4 gm/100 sq in/24 hr	6.2 gm/msq/24 hr
Service Temperature Range	32 F to 160 F	0 C to 71 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

