

DF 642



INDUSTRIAL GRADE, DOUBLE-COATED CLOTH TAPE

TYPICAL APPLICATIONS

- For carpet and pad installation at convention center, arenas and hotels
- Used for general purpose holding and mounting applications
- Can also be used to hold signs and dispensers for POP merchandising

PRODUCT FEATURES

- Adheres to smooth and irregular surfaces
- Conformable

CONSTRUCTION

Overall Grade/Function: Industrial

Backing: Polyester/cotton blend cloth

Adhesive: Synthetic rubber

Liner: Siliconized, flat paper release liner

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

23 m

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



WHITE
(WHI)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	32 lbs/in width	56.0 N/10 mm
Adhesion to Stainless Steel - Liner Side	39 oz/in width	4.27 N/10 mm
Adhesion to Stainless Steel - Exposed Side	32 oz/in width	3.50 N/10 mm
Thickness (Without Liner)	12 mils	0.30 mm
Elongation	8%	8%
Service Temperature Range	50 F to 225 F	10 C to 107 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

