

PP 802

Shurtape®
TRUE TO YOUR WORK™

PREMIUM PLUS GRADE SOLVENT-BASED ACRYLIC PACKAGING TAPE

TYPICAL APPLICATIONS

- For light to medium duty sealing, repairing and bundling of corrugated cartons, paper and film containers
- Use with a hand-held or machine dispenser

PRODUCT FEATURES

- High initial tack
- Excellent holding power
- Performs in a range of temperatures

CONSTRUCTION

Overall Grade/Function: Premium Plus
Backing: 25 micron biaxially oriented polypropylene cast film
Adhesive: Solvent-based acrylic

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

914 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

CID A-A-1684C

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

| | STANDARD | METRIC |
|-------------------------------|-----------------|---------------|
| Tensile Strength | 22 lbs/in width | 38.5 N/10 mm |
| Adhesion to Stainless Steel | 25 oz/in width | 2.74 N/10 mm |
| Thickness | 2.0 mils | 0.05 mm |
| Elongation | 140% | 140% |
| Application Temperature Range | 20 F to 110 F | -7 C to 43 C |
| Service Temperature Range | -20 F to 180 F | -29 C to 82 C |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

