

# RT 700



# T-REX<sup>®</sup>

**FEROCIOUSLY STRONG TAPE<sup>®</sup>**

## T-REX<sup>®</sup> CLEAR REPAIR TAPE



### TYPICAL APPLICATIONS

- For quick and discreet repairs to a variety of surfaces, including those that require a water-resistant seal
- Can be applied to wet\* or dry surfaces
- Can also be applied to rough surfaces at below freezing temperatures
- For indoor and outdoor use

### PRODUCT FEATURES

- All-weather performance
- Versatile and conformable
- UV-resistant to prevent yellowing and to maintain product performance and integrity
- Pinked edge for hand-tearability with clean edge
- Aggressive adhesion
- Waterproof and water-resistant (after application to surface)
- Puncture-resistant, crystal clear backing

### CONSTRUCTION

Overall Grade/Function: Repair  
Backing: Ionomer film  
Adhesive: Solvent acrylic-based

### STANDARD WIDTH(S)

1.88 in

### STANDARD LENGTH(S)

9 yd

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean and free of grease, oil or other contaminants.

### COLOR(S)



**CLEAR**  
(CLR)

### PHYSICAL PROPERTIES      STANDARD      METRIC

Tensile Strength	23.5 lbs/in width	41.2 N/10 mm
Adhesion to Stainless Steel	100 oz/in width	10.95 N/10 mm
Thickness	6.8 mils	0.17 mm
Elongation	430%	430%
Holding Power to Steel	1,800+ minutes	1,800+ minutes
Service Temperature Range	-5 F to 150 F	-20 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

\* Follow recommended usage instructions for best results in wet-stick applications.



# Shurtape

TECHNOLOGIES