

# CP 27P

**Shurtape®**  
TRUE TO YOUR WORK™

## PRINTED FLOOR MARKING TAPE



### TYPICAL APPLICATIONS

- Great for temporary indoor floor marking, including to support social distancing efforts
- Removes cleanly from most flooring surfaces up to 60 days
- Not recommended for use on hardwood floors

### PRODUCT FEATURES

- Medium adhesion
- UV-resistant
- Easy, no-residue removal

### CONSTRUCTION

Overall Grade/Function: Premium  
Backing: Fine structured crepe paper  
Adhesive: Rubber-based

### STANDARD WIDTH(S)

48 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22.5 lbs/in width	39.4 N/10 mm
Adhesion to Stainless Steel	32.5 oz/in width	3.56 N/10 mm
Thickness	5.08 mils	0.13 mm
Elongation	10%	10%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

