

CP 905



HIGH PERFORMANCE GRADE, HIGH TEMPERATURE MASKING TAPE

TYPICAL APPLICATIONS

- For high temperature - up to 350 F - paint masking and metal fabrication applications in the transportation (auto, coaches, buses and marine) industry
- Recommended for indoor use only

PRODUCT FEATURES

- High adhesion
- Easy to unwind
- High initial tack and good adhesion to itself
- Clean, flat edges for sharper paint lines
- Residue-free removal
- High temperature stability through multiple bake cycles
- Temperature resistant up to 350 F
- Heavy duty crepe backing is tear- and sliver-resistant

CONSTRUCTION

Overall Grade/Function: High Performance

Backing: Fine structured crepe (FSC)

Adhesive: Rubber-based

STANDARD WIDTH(S)

24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

COLOR(S)



NATURAL
(NAT)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	24 lbs/in width	42 N/10 mm
Adhesion to Stainless Steel	41 oz/in width	4.49 N/10 mm
Thickness	6.4 mils	0.16 mm
Elongation	11%	11%
Service Temperature Range	60 F to 350 F	16 C to 176 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

