

# FT 175



## TYPICAL APPLICATIONS

- For insulating and wrapping electrical splices and connections
- Protects wire and cables

## PRODUCT FEATURES

- Excellent adhesion
- Exceptional tensile strength
- Good abrasion resistance
- Tightly wraps and overlaps most held surfaces and easy to tear by hand

## CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: Cloth

Adhesive: Natural rubber

## STANDARD WIDTH(S)

3/4 in 19.05 mm

## STANDARD LENGTH(S)

60 ft 18.25m

Contact your Shurtape sales representative for other available sizes

## STANDARD CORE SIZE

1.25 in

## STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

## COLOR(S)



Black (BLK)

PHYSICAL PROPERTIES	STANDARD	METRIC
Thickness	12 mils	0.30 mm
Tensile Strength	46.4 lbs/in width	81.3 N/10 mm
Elongation	5%	5%
Service Temperature Range	15 F to 176 F	-10 C to 80 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

