

FOAM PIPE WRAP INSULATION TAPE

TYPICAL APPLICATIONS

- For hot and cold pipe insulation applications – cover hot pipes to prevent heat loss and cold pipes to prevent condensation drip

PRODUCT FEATURES

- Aggressive adhesion
- Lined
- Adheres firmly to all metals
- Thermal conductivity is 0.28 at 75 F, in accordance with ASTM C-177

CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: Nitrile Butadiene Rubber (NBR) polymeric foam; closed cell elastomeric insulation

Liner: Non-contaminating, siliconized release liner

Adhesive: Acrylic-based

STANDARD WIDTH(S)

50.8 mm

STANDARD LENGTH(S)

9.14 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength (Longitudinal)	6 lbs/in width	10.5 N/10 mm
Thickness (With Liner)	122 mils	3.1 mm
Thickness (Without Liner)	118.1 mils	3.0 mm
Elongation (Machine Direction)	126%	126%
Service Temperature Range	-20 F to 180 F	-29 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

