

# PXL BR



## BR CODE™ HEAVY-DUTY PERMANENT SCANNABLE LABELS

STICK. SCAN. CONNECT™

### TYPICAL APPLICATIONS

- For connecting physical locations to critical, digital information, such as photos, text, maintenance documentation, video links, voice memos, instructions, GPS location data and more
- Can be used in rugged environments

### PRODUCT FEATURES

- Extremely durable, individual labels for easy use
- Easy to adhere to a range of surfaces and substrates
- Weather- and chemical-resistant
- Recommended for indoor or outdoor use on flat surfaces
- Permanent adhesion
- Information is easily accessible via a mobile device and app
- Unlimited, safe and secure storage of critical information in one centralized repository

### CONSTRUCTION

Overall Grade/Function: Specialty  
Backing: Heavy-duty polypropylene  
Adhesive: Acrylic-based adhesive  
Liner: Paper

### STANDARD ROLL WIDTH(S)

1.73 in 44 mm

### STANDARD ROLL LENGTH(S)

11.5 ft 3.5 m (100 codes)

Contact your Shurtape sales representative for other available sizes

### INDIVIDUAL LABEL SIZE

1.2 in x 1.73 in 30 mm x 44 mm

### STANDARD CORE SIZE

1.5 in

### APPLICABLE STANDARDS

Conforms to BS 5609

### COLOR(S)



**YELLOW**  
(YEL)

PHYSICAL PROPERTIES	STANDARD	METRIC
---------------------	----------	--------

Adhesion to Stainless Steel	32 oz/in width	3.5 N/10 mm
Thickness (With Liner)	7.3 mils	0.19 mm
Thickness (Without Liner)	4.1 mils	0.10 mm
Service Temperature Range	-40 F to 200 F	-40 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE AND USAGE CONDITIONS

Labels should be stored in their original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which label is applied should be clean, dry and free of grease, oil or other contaminants.



### BITRIP® APP

The BitRip® App is available for free download from the Apple App Store for Apple devices or Google Play store for Android devices.