

# TG 356



## PREMIUM PERFORMANCE GRADE ADHESIVE TRANSFER TAPE

### TYPICAL APPLICATIONS

- For mounting, holding, joining and splicing various substrates, including paper, cardboard, textiles, plastics, leather, wood, glass and painted surfaces
- For use on displays, POS, posters, etc.
- Use with an adhesive transfer gun to make almost any surface self-adhesive

### PRODUCT FEATURES

- Quick and easy to use
- Eliminates the clean-up and drying time associated with liquid adhesives
- Maintains adhesion characteristics in normal and severe environmental conditions
- Extremely conformable
- Resists humidity, most solvents and UV light

### CONSTRUCTION

Overall Grade/Function: Premium Performance

Adhesive: Unsupported, permanent, dry acrylic-based adhesive reverse wound on 1" I.D. core

Liner: Non-contaminating, siliconized, tan, paper release liner

### STANDARD WIDTH(S)

12 mm    19 mm

### STANDARD LENGTH(S)

33 m

Contact your Shurtape sales representative for other available sizes

### STANDARD CORE SIZE

1 in

### COLOR(S)



**CLEAR**  
(CLR)

PHYSICAL PROPERTIES	STANDARD	METRIC
Adhesion to Stainless Steel	32 oz/in width	3.50 N/10 mm
Thickness (With Liner)	5.5 mils	0.14 mm
Thickness (Without Liner)	2 mils	0.05 mm
Service Temperature Range	-60 F to 250 F	-51 C to 121 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

