

GENERAL PURPOSE GRADE TRANSPARENT CELLULOSE FILM TAPE

TYPICAL APPLICATIONS

- For sealing, packaging and mending applications, particularly involving hard-to-stick-to surfaces
- Also used for splicing applications

PRODUCT FEATURES

- Adheres to hard-to-stick-to surfaces
- High tensile strength
- Hand-tearable
- Static-free in accordance with Afera Test Method 4011 - "Electric Strength of Adhesive Tape"

CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: Transparent cellulose film

Adhesive: High-tack, rubber-based

STANDARD WIDTH(S)

12 mm 18 mm 24 mm

STANDARD LENGTH(S)

66 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

CID A-A-113D, Type 1, Class A

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	35 oz/in width	3.83 N/10 mm
Thickness	1.7 mils	0.04 mm
Elongation	18%	18%
Maximum Service Temperature	265 F	129 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

