

P-661

Shurtape®
TRUE TO YOUR WORK™

GLOW-IN-THE-DARK SPECIALTY GAFFER'S TAPE

TYPICAL APPLICATIONS

- For safety marking
- Can also be used for a multitude of applications in the audio/visual, television, photography, theatrical and motion picture industries
- Other applications include labeling and marking various objects, such as safety/critical equipment, exit/directional signage, tripping hazards, access handles, sports equipment and tools

PRODUCT FEATURES

- High adhesion and tack
- Conforms to complex 3D surfaces
- Writable/printable with a non-smearing surface
- Hand-tearable in both directions
- Residue-free removal
- Premium photo luminescent pigment provides increased glow intensity and extended glow duration

CONSTRUCTION

Overall Grade/Function: Specialty Gaffer's
Backing: Coated cloth with photo luminescent pigment
Adhesive: Synthetic rubber

STANDARD WIDTH(S)

1 in 2 in

STANDARD LENGTH(S)

10 yd 20 yd

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

ASTM E2072; Meets Consumer Product Safety Commission requirements through conformance with ASTM D-4236

This product has been found to conform to the Consumer Product Safety Commissions' (CPSC) "Labeling of Hazardous Art Materials Act" (LHAMA) using a third-party toxicologist under ASTM D-4236. LHAMA requires that arts & crafts products sold in the U.S. be reviewed in this manner to determine if any hazardous materials are present through normal product use and to warn consumers if such hazardous materials exist through specific language dictated by a toxicologist. The statement "Conforms to ASTM D-4236" indicates a toxicologist has reviewed the product and has found no hazardous materials present that would require a warning statement.

COLOR(S)



PHYSICAL PROPERTIES STANDARD METRIC

Tensile Strength	50 lbs/in width	87.6 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness	13 mils	0.33 mm
Elongation	4%	4%
Service Temperature Range	50 F to 180 F	10 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

